



SolarEdge Power Optimizer

P300 / P320 / P370 / P400 / P405



POWER OPTIMIZER

PV power optimization at the module-level

- Up to 25% more energy
- Superior efficiency (99.5%)
- Mitigates all types of module mismatch losses, from manufacturing tolerance to partial shading
- Flexible system design for maximum space utilization
- Fast installation with a single bolt
- Next generation maintenance with module-level monitoring
- Module-level voltage shutdown for installer and firefighter safety



SolarEdge Power Optimizer

P300 / P320 / P370 / P400 / P405

	P300 (for 60-cell modules)	P320 (for high-power 60-cell modules)	P370 (for higher-power 60 and 72-cell modules)	P400 (for 72 & 96-cell modules)	P405 (for thin film modules)	
INPUT						
Rated Input DC Power ⁽¹⁾	300	320	370	400	405	W
Absolute Maximum Input Voltage (Voc at lowest temperature)	48		60	80	125	Vdc
MPPT Operating Range	8 - 48		8 - 60	8 - 80	12.5 - 105	Vdc
Maximum Short Circuit Current (Isc)	10	11		10.1		Adc
Maximum DC Input Current	12.5	13.75		12.63		Adc
Maximum Efficiency	99.5					%
Weighted Efficiency	98.8					%
Oversoltage Category	II					
OUTPUT DURING OPERATION (POWER OPTIMIZER CONNECTED TO OPERATING SOLAREEDGE INVERTER)						
Maximum Output Current	15					Adc
Maximum Output Voltage	60			85		Vdc
OUTPUT DURING STANDBY (POWER OPTIMIZER DISCONNECTED FROM SOLAREEDGE INVERTER OR SOLAREEDGE INVERTER OFF)						
Safety Output Voltage per Power Optimizer	1					Vdc
STANDARD COMPLIANCE						
EMC	FCC Part15 Class B, IEC61000-6-2, IEC61000-6-3					
Safety	IEC62109-1 (class II safety), UL1741					
RoHS	Yes					
INSTALLATION SPECIFICATIONS						
Maximum Allowed System Voltage	1000					Vdc
Compatible inverters	All SolarEdge Single Phase and Three Phase inverters					
Dimensions (W x L x H)	128 x 152 x 27.5 / 5 x 5.97 x 1.08			128 x 152 x 35 / 5 x 5.97 x 1.37	128 x 152 x 50 / 5 x 5.97 x 1.96	mm / in
Weight (including cables)	630 / 1.4			750 / 1.7	845 / 1.9	gr / lb
Input Connector	MC4 Compatible	MC4 / Amphenol AH4 Double Insulated;		MC4 Compatible		
Output Wire Type / Connector	Double Insulated; MC4 Compatible		MC4 / Amphenol AH4	Double Insulated; MC4 Compatible		
Output Wire Length	0.95 / 3.0		1.2 / 3.9			m / ft
Operating Temperature Range	-40 - +85 / -40 - +185					°C / °F
Protection Rating	IP68 / NEMA6P					
Relative Humidity	0 - 100					%

⁽¹⁾ Rated STC power of the module. Module of up to +5% power tolerance allowed.

PV SYSTEM DESIGN USING A SOLAREEDGE INVERTER ⁽²⁾⁽³⁾	SINGLE PHASE HD-WAVE	SINGLE PHASE	THREE PHASE 208V	THREE PHASE 480V	
Minimum String Length (Power Optimizers)	8		10	18	
Maximum String Length (Power Optimizers)	25		25	50	
Maximum Power per String	5700 (6000 with SE7600H-US)	5250	6000	12750	W
Parallel Strings of Different Lengths or Orientations	Yes				

⁽²⁾ For detailed string sizing information refer to: http://www.solaredge.com/sites/default/files/string_sizing_na.pdf.

⁽³⁾ It is not allowed to mix P405 with P300/P370/P400/P600/P700 in one string.

